

DeIPAC® 2950
Aluminum Chloride Hydroxide Sulfate

The DeIPAC series includes DeIPAC 2950, which has become widely accepted as the polyaluminum chloride of choice for cost effective improvement of finished water quality. When used as a coagulant DeIPAC can provide longer filter runs, reduce or eliminate the need for alkali pH adjustment, and reduce sludge residuals. DeIPAC 2950 meets the specifications of the American Water Works Association Standard B408-10 and complies with the requirements of NSF/ANSI 60: Drinking Water Treatment Chemicals – Health Effects at a maximum dosage of 250 mg/L.

PROPERTIES

Appearance: Color may vary
Specific Gravity @60°F: 1.31 ± 0.02
Product Weight: ~10.93 Lbs. /US
Gallon
pH (neat): 2.6 ± 0.5
Freezing Point 10°F

SPECIFICATIONS

% Al₂O₃ 17.75 ± 0.5
% Al 9.4 ± 0.3
% Basicity 79 ± 2
% Sulfate 1.0 ± 0.5

PRINCIPAL USES

Drinking water / wastewater treatment –
removal of suspended matter and phosphorus

SAFETY / HANDLING

Observe caution when handling corrosive materials. Please consult the material safety data sheet (MSDS) for safety and handling precautions.

DELIVERY

275 gallon IBCs (totes), tank trucks and railcars

PRODUCTION

USALCO has production facilities in:

- Baltimore, Maryland
- Fairfield, Ohio

CUSTOMER SERVICE

If you have any questions concerning this material, please contact our Inside Sales Department at:

410-918-2230 or **info@usalco.com**