



# Technical Data Sheet

## USALCO® Ground Aluminum Sulfate Low Iron Grade

USALCO's dry aluminum sulfate (alum) is manufactured using a state of the art process and high quality raw materials ensuring that it meets the highest quality standards. USALCO produces dry alum in various grades (Low-Iron, Iron-Free, FCC Grade) as well as specialty granular sizes to satisfy even the most difficult applications. USALCO's dry alum is used in water treatment, colors and dyes, leather tanning, paper making as well as many other industrial applications. USALCO dry alum meets the specifications of the American Water Works Association Standard B403-16 and complies with the requirements of NSF/ANSI 60: Drinking Water

### SPECIFICATIONS

% Al <sub>2</sub> O <sub>3</sub> :	17.0 -17.5
Iron (Fe):	10-100 ppm
% Insoluble	< 0.05

### Particle Size:

Through 4 Mesh	0%
Through 10 Mesh	≥ 90%

### PRINCIPAL USES

Drinking water / wastewater treatment – removal of suspended matter and phosphorus

### SAFETY / HANDLING

Observe caution when handling corrosive materials. Please consult the safety data sheet (SDS) for safety and handling precautions.

### DELIVERY

50 lb bags, FIBC (supersacks), and bulk (pneumatic trailer)

### PRODUCTION

USALCO has production facilities in:

- Baltimore, Maryland

### CUSTOMER SERVICE

If you have any questions concerning this material, please contact our Inside Sales Department at:

**410-918-2230** or [info@usalco.com](mailto:info@usalco.com)