



Technical Data Sheet

USALCO® 38 Sodium Aluminate Solution, 38% Solids

USALCO 38 is an economical source of highly reactive alumina manufactured by dissolving alumina tri-hydrate (ATH) into sodium hydroxide and water. USALCO 38 is also stabilized to prevent alumina from precipitating. The use of only stringently selected raw materials and state-of-the-art manufacturing practices ensures that USALCO 38 is of the highest quality. USALCO 38 meets the specifications of the American Water Works Association Standard B405-16 and complies with the requirements of NSF/ANSI 60: Drinking Water Treatment Chemicals -Health Effects at a maximum dosage of 105 mg/L.

PROPERTIES

| | |
|-------------------------|--|
| Chemical Formula: | Na ₂ Al ₂ O ₄ |
| Appearance: | Amber Liquid |
| Specific Gravity @60°F: | 1.46 - 1.49 |
| Product Weight::: | 12.18 - 12.43 Lbs./Gal |
| pH (neat): | 14 |
| pH (1% solution): | >11.5 |
| Viscosity (cps): | 155 @25C 80@45C |

SPECIFICATIONS

| | |
|--|--------------|
| % Al ₂ O ₃ : | 19.5 - 20.5 |
| % Na ₂ O: | 17.9 - 19.1 |
| % Na ₂ Al ₂ O ₄ : | 31.4 - 33.0 |
| Molar Ratio (Na ₂ O / Al ₂ O ₃): | 1.48 - 1.54 |
| Iron (Fe): | 200 ppm, max |
| Silica: | 200 ppm, max |

PRINCIPAL USES

Drinking water / wastewater treatment – removal of suspended matter and phosphorus.

Catalyst, zeolite, molecular sieve manufacturing.

Coating for titanium dioxide pigments.

Pulp and paper manufacturing – pitch control and sizing agent.

SAFETY/HANDLING

Observe caution when handling corrosive materials. Please consult the safety data sheet (SDS) for safety and handling precautions.

DELIVERY

275 gallon IBCs (totes), tank trucks and railcars

PRODUCTION

USALCO has production facilities in:

- Baltimore, Maryland
- Fairfield, Ohio
- Michigan City, Indiana
- Ashtabula, Ohio
- Port Allen, Louisiana

CUSTOMER SERVICE

If you have any questions concerning this material, please contact our Inside Sales Department at:

410-918-2230 or info@usalco.com